REPORT DOCUMENTATION PAGE

Form Approved

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Artington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information.

collection of information if it do	es not display a currently val	id OMB control number. PLEASE	DO NOT RETURN YOUR FORM	TO THE ABOVE ADDI	RESS.
1. REPORT DATE (DE	D-MM-YYYY)	2. REPORT TYPE Technical Papers		3. [DATES COVERED (From - To)
4. TITLE AND SUBTIT	LE	1 comment apers		5a.	CONTRACT NUMBER
				5b.	GRANT NUMBER
				5c.	PROGRAM ELEMENT NUMBER
6. AUTHOR(S)	· · · · · · · · · · · · · · · · · · ·			5d. 305	PROJECT NUMBER
				5e. RD	TASK NUMBER 3D
				1	WORK UNIT NUMBER
7. PERFORMING ORG	GANIZATION NAME(S) AND ADDRESS(ES)			PERFORMING ORGANIZATION PORT
Air Force Research AFRL/PRS 5 Pollux Drive Edwards AFB CA		C)			
9. SPONSORING / MC	INITORING AGENCY	NAME(S) AND ADDRES	SS(ES)		SPONSOR/MONITOR'S RONYM(S)
Air Force Research	Laboratory (AFMC	E)		11	SPONSOR/MONITOR'S
AFRL/PRS 5 Pollux Drive					NUMBER(S)
Edwards AFB CA 9	3524-7048			AF	RL-PR-ED-TP-1998-113
12. DISTRIBUTION / A	VAILABILITY STAT	EMENT			
Approved for public	release; distribution	on unlimited.			
13. SUPPLEMENTAR	YNOTES				
14. ABSTRACT				· · · · · · · · · · · · · · · · · · ·	
			5	חבחח	127 170
				UCUU.	127 170
15. SUBJECT TERMS					
16. SECURITY CLASS	SIFICATION OF:		17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON Leilani Richardson
a. REPORT	b. ABSTRACT	c. THIS PAGE			19b. TELEPHONE NUMBER
Unclassified	Unclassified	Unclassified	A		(include area code) (661) 275-5015

MEMORANDUM FOR IN-HOUSE PUBLICATIONS

FROM: PROI (TI) (STINFO)

10 Jul 98

SUBJECT: Authorization for Release of Technical Information, Control Number: AFRL-PR-ED-TP-1998-113

C.W. Beckman, R.L. Geisler "The History of the BATES Motor at RPL

AIAA slides

(Statement A)



THE HISTORY OF THE BATES MOTOR AT RPL

AIR FORCE RESEARCH LABORATORY CHARLES W. BECKMAN GEISLER ENTERPRISES ROBERT L. GEISLER

INITIAL BATES FIRING - Sept 1961






BATES



A highly accurate test motor system for ballistic prediction, assessment and comparison.




15-lb and 70-lb BATES Motor Design



15-pound 70-pound	1000.	2.	17.	20.	12.	8
15-poun	1000.		8.	12.	6.75	4.6
Motor size	Pressure (psi)	Nozzle Diameter (บูมูเรอ)	Gas Residence Time (msec)	Grain Length (in) (A)	Grain Outside Diameter (in) (B) 6.75	Grain Port Diameter (in) (C)


Standard 70-1b BATES Motor









Vacuum Ballistics Testing



70 Pound Reusable BATES Motor




Super BATES Reusable Motor






15-lb and 70-lb BATES Burnback History



Motor size Neutrality (max/ave/min) Port/Throat Ratio

15-pound/70-pound 1.01/1.00/0.97 ~30

Ballistic Anomaly Phenomena







BATES DELIVERED SPECIFIC IMPULSE

ESTIMATED ERROR

+ 0.25 seconds

70-pound thrust accuracy + 0.10 %

15-pound thrust accuracy + 0.25 %

3 70-pound firings required for this precision

6 15-pound firings required for this precision

+ 0.10 seconds

6 70-pound firings required for this precision

9 15-pound firings required for this precision



BATES Test History

Motor Firings

Approximately 4000 test firings

Propellant Evaluations

Approximately 400 formulations evaluated




SPECIFIC IMPULSE EFFICIENCY INFLUENCES


- COMBUSTION EFFICIENCY
- **HEAT LOSS**
- **DIVERGENCE LOSSES**
- TWO-PHASE FLOW LOSSES
- MULTIPHASE MOMENTUM LOSSES
- MULTIPHASE TEMPERATURE NON-EQUILIBRUM
- CHEMICAL RECOMBINATION LOSSES
- FRICTIONAL LOSSES

A STANDARD OF THE STANDARD OF

Particle Size vs Throat Diameter



Delivered Isp vs Mass Flow Rate







Varying Aluminum Propellant Formulations

Wt% AI	15.	18.	21.	24.	27.	30.
	75.	72.	.69	.99	63.	.09
Wt% HTPB	10.	10.	10.	10.	10.	10.
Rb 1000 psia	0.56	0.55	0.56	0.46	0.51	0.50
ղ ^{լչ} (ISP)15-Ib	92.30	91.27	90.48	89.59	89.11	88.89
η^{15} (ISP) 70-1b	93.38	92.84	92.03	91.31	90.92	90.51
Tc(K)@1000psi	3602.	3682.	3746.	3784.	3787.	3743.
T*(K) no Al	2859.	2791.	2705.	2605.	2494.	2376.
gm.	0.269	0.319	0.362	0.396	0.413	0.415
Al, O, at Thrt						

Initial BATES Scaling Approach











BATES LaserParticle Size Measurements








Initial Recession Analysis




Thrust/Pressure Analysis






Isp Efficiency Vs Spin "G" Level (70 lb BATES






* Land State of the state of th

Dual Chamber Staged Combustion Feasibility Motor



Performance Increase from **Hydrogen Augmentation**







Summary

BATES is an Invaluable Assessment Tool

- Provides Precision Measurements
- Simple and Analyzable Hardware
- Adaptable to Tactical, Strategic or Space Needs Irreplaceable Propellant and Ballistic Database